REV	REVISION RECORD
A	RELEASE











DESCRIPTION	ØD
REVERB, 30.9	30.9+0/-0.07
REVERB, 31.6	31.6+0/-0.07
REVERB, 34.9	34.9+0/-0.07

DESCRIPTION	L1	L2	L3	(TRAVEL)
REVERB 340MM LONG X 100MM TRAVEL	340	175	80	100
REVERB 390MM LONG X 125MM TRAVEL	390	200	80	125
REVERB 440MM LONG X 150MM TRAVEL	440	225	80	150
REVERB 480MM LONG X 170MM TRAVEL	480	245	80	170

NOTES (UNLESS OTHERWISE SPECIFIED):

1. SRAM RESERVES THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE.
2. REFERENCE DIMENSIONS NOTED WITH "( )" ARE FOR CUSTOMER DESIGN INFORMATION ONLY.

[3] APPLIES TO DISCRETE AND MMX MODELS

[4] VERTICAL LENGTH REQUIRED FOR FULL BEND RADIUS

[5] MINIMUM FRAME INSERTION

6. MEASURED EXPOSED HOSE LENGTH SHOULD BE THE MODEL SPECIFIED HOSE LENGTH MINUS 0 - 15MM

ALL DIMENSIONS ARE mm
THIRD ANGLE PROJECTION

MASS (g): 0.0

MATERIAL: N/A

GEOMETRIC DIMENSIONING AND TOLERANCING TO BE INTERPRETED PER ASME Y14.5-2009

• INDICATES THE DIMENSION IS CRITICAL TO THE FORM, FIT OR FUNCTION OF THE PART OR PRODUCT

UNTOLERANCED LENGTH DIMENSIONS(mm)	
LENGTH DIMENSIONS	TOLERANCE
from 0.5 up to 6	± 0.1
over 6 up to 30	± 0.2
over 30 up to 120	± 0.3
over 120 up to 400	± 0.5
UNTOLERANCED ANGLE DIMENSIONS	± 2°

DESIGNED BY: R CHAMBERS

FORMAT: A2 | SCALE: 4:5 | SHEET: 1 / 1

LIFECYCLE STATUS: Released

SRAM.
CONFIDENTIAL - THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SRAM CORPORATION AND MAY NOT BE DISCLOSED WITHOUT PERMISSION.

DRAWING NAME / DESCRIPTION: USER SPEC REVERB STEALTH CJ

DRAWING NUMBER: 98-6815-017-000

VERSION: A.1