


# CAMBER PRO

Select Bike Model

WO ERHÄLTLICH ›

360

Ansicht in Red/Black





## TECHNISCHE SPEZIFIKATIONEN

| | |
|---|---|
| RAHMEN | M4 hydroformed tubing, sealed cartridge bearing pivots, disc only, Command Post routing, replaceable derailleur hanger, bolt on cable guides, 120mm travel |
| DÄMPFER | Custom Fox Triad II for Specialized, custom on-the-fly 3-position switch 1) lock out 2) Open 3) ProPedal, rebound adj., 7.875x2.0" |
| GABEL | Fox F120 RL, air spring, reb adj., LO, standard drop-outs, disk, 120mm travel |
| STEUERSATZ | 1 1/8" upper and lower campy style cartridge bearings for integrated alloy HT |
| VORBAU | Specialized XC, 3D forged alloy, 4-bolt, 31.8mm clamp, adjustable rise |
| LENKER | Specialized XC low-rise bar, 7050 butted alloy, 680mm wide, 8 degree back sweep, 6 degree up, 31.8mm |
| LENKERGRIFFE | Specialized lock-on, S/M: Grappler, Other: Rocca |
| VORDERRADBREMSE | Custom Avid Elixir R SL, hydraulic disc, reach adjust, alloy backed semi-metallic pads, stainless hardware, G3 Clean Sweep rotor, S/M: 185mm, L/XL: 203mm |
| HINTERRADBREMSE | Custom Avid Elixir R SL, hydraulic disc, reach adjust, alloy backed semi-metallic pads, stainless hardware, G3 Clean Sweep rotor, S/M: 160mm, L/XL: 185mm |
| BREMSHEBEL | Custom Avid Elixir R SL hydraulic, tool-less reach adj. |
| UMWERFER | SRAM X.7 10-speed, S3 direct mount for DMD, bottom pull |
| SCHALTWERK | Shimano RD-M980 XTR Shadow, 10-speed, long cage |
| SCHALTHEBEL | Shimano SL-M660-10R SLX, 10-speed, trigger |
| KASSETTE | Shimano HG81, 10-speed, 11-36t |
| KETTE | KMC X10, 10-speed, w/ reuseable Missing Link, nickel plates |
| KURBELGARNITUR | Custom SRAM Carbon S-2200, 10-speed XC Trail double, GXP spindle, removeable spider, S: 170mm, others: 175mm |
| KETTENBLÄTTER | 38A x 24A, 4-bolt, 104/64mm |
| INNENLAGER | SRAM GXP, outboard bearing |
| PEDALE | Resin Test Ride Pedals with toe clips, CEN std. |
| FELGEN | Custom DT Swiss X420SL, 24mm w/ eyelets, 28/32h |
| VORDERRADNABE | Specialized Hi Lo disc, laser-etched logo, OS 24 end caps, sealed cartridge bearing, RWS, 28h |
| HINTERRADNABE | Specialized Hi Lo disc, lasere-etched logo, double sealed cartridge bearing, QR, 32h |
| SPEICHEN | 1.8mm (15g) stainless |
| VORDERREIFEN | S-Works "The Captain", 120 TPI, 2Bliss ready aramid bead, dual compound, 26x2.0" |
| HINTERREIFEN | Specialized "The Captain" Control, 60 TPI, 2Bliss ready aramid bead, dual compound, 26x2.0" |

| | |
|---|---|
| SCHLÄUCHE | Ultralight presta valve |
| SATTEL | Specialized BG Henge Comp, hollow Cr-Mo rails, 143mm width |
| SATTELSTÜTZE | 2014 butted alloy, single bolt setback, 30.9mm, S/M: 350mm, others: 400mm |
| SATTELSTÜTZKLEMME | 34.9mm clamp ID, alloy collar w/ QR, black |
| ANMERKUNGEN | Protective clear coat, derailleur hanger, reflectors, owners manual |

Technische Änderungen vorbehalten.

ÜBERSICHT GEOMETRIE ›



Specialized Bicycle Components. All rights reserved.