

Rim-/tire-width and pressure specifications

tire width		rim width					
		17mm	19mm	22mm	25mm	30mm	35mm
		maximum pressure bar					
23mm	0.90"	8,00	8,00				
25mm	1.00"	7,50	7,50				
28mm	1.10"	7,50	7,50				
30mm	1.20"	6,50	6,50				
32mm	1.25"	5,50	5,50				
33mm	1.30"	5,50	5,50	3,00			
35mm	1.40"	5,00	5,00	3,00			
38mm	1.50"	4,00	4,00	3,00			
40mm	1.60"	4,00	4,00	3,00	3,00		
45mm	1.80"	3,50	3,50	3,00	3,00		
50mm	2.0"		3,00	3,00	3,00	2,50	
53mm	2.1"			2,80	2,80	2,50	
55mm	2.2"			2,60	2,60	2,50	2,30
58mm	2.3"			2,40	2,40	2,40	2,30
61mm	2.4"			2,20	2,20	2,20	2,20
63mm	2.5"			2,10	2,10	2,10	2,10
66mm	2.6"				2,00	2,00	2,00
68mm	2.7"				1,90	1,90	1,90
71mm	2.8"				1,80	1,80	1,80
76mm	3.0"					1,70	1,70

ideal combination

possible combination

NEWMEN

rim width					
17mm	19mm	22mm	25mm	30mm	35mm
maximum pressure psi					
116	116				
108	108				
108	108				
94	94				
80	80				
80	80	43			
72	72	43			
58	58	43			
58	58	43	43		
50	50	43	43		
	43	43	43	36	
		40	40	36	
		37	37	36	33
		34	34	34	33
		32	32	32	32
		30	30	30	30
			29	29	29
			27	27	27
			26	26	26
				25	25