

DOWNHILL

SUMMUM CARBON RR

Matte Carbon UD / Gloss Racing Silver

FRAME Summum Carbon Stealth Air full Carbon, Zero Suspension System, 200mm travel, Forward Geometry,

Carbon Monoblock upper link, SuperBoost 12x157mm rear axle, 83mm BSA bottom bracket, HHG internal cable routing, MAX. capacity dual raw Enduro bearings, shock mudquard, ISCG 05, custom

frame protectors. *Geometry kit included

SIZES S/M/L/XL29" and MX

REAR SHOCK Fox DHX2 Factory Kashima, 225x70mm. Settings: high and low-speed compression, high and

low-speed rebound, spring preload. Super light steel (SLS) spring. Trunnion top mount, 30x8mm

bottom bushings

SHOCK SETTINGS ECCO10 compression, ECR012 rebound. Spring rate: S size 400 lbs, M size 450 lbs, L/XL size 500 lbs

FORK Fox 40 29 Float FIT GRIP2 EVOL Factory Kashima, 203mm, air spring, 1-1/8" steerer tube, 20x110mm axle,

offset 56mm. Settings: high and low-speed compression, high and low-speed rebound, air preload

HEADSET Onoff Mercurium 1.5 ZS for 1-1/8" steerer tube, 41x30.15x7x45° ACB sealed bearings, geometry kit

cups, external diameter 56mm

STEM Onoff Krypton DH CNC Integrated FG, 25-30mm adjustable length, 31.8mm barbore, 6061 alloy,

2x6mm spacer

HANDLEBAR Renthal Fatbar series 7 alloy, rise: 30mm, width: 800mm, 7° backsweep, 5° upsweep, 31.8mm barbore

GRIPS Renthal, double lock-on, kevlar compound, 130mm

SEATPOST SDG Micro I-Beam SP-951 Carbon, diameter 31.6mm, length 300mm, micro-adjustment

SADDLE SDG I-Fly 2.0 I-Beam, high-density PU foam, Cordura sides

FRONT BRAKE Shimano Saint M820, 4-piston caliper, RT86 203mm 2-piece IS 6 bolts rotor with ICE technology,

resin pads with cooler

REAR BRAKE Shimano Saint M820. 4-piston caliper, RT86 203mm 2-piece IS 6 bolts rotor with ICE technologu.

resin pads with cooler

BRAKE LEVER Shimano Saint, ergonomic antiskid lever with servo wave, free stroke and tool less reach adjust

RIMS e*thirteen LG1 Race Carbon, IW30 29" Hookless, World Cup carbon fiber, 30mm internal width,

tubeless ready, 32 spokes

SPOKES e*thirteen custom Hive triple-butted black alloy, alloy nipples, nipple washers

FRONT HUB e*thirteen Boost 20x110mm. triple-sealed. fullu machined aluminum. IS 6 bolts

REAR HUB e*thirteen Superboost 12x157mm, triple-sealed, fully machined aluminum w/6-degree engagement,

IS 6 bolts

FRONT TIRE Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing,

wire bead

REARTIRE Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing,

wire beac

CRANKSET Shimano Saint M825 Hollowtech II, reinforced steel axle, 165mm

RINGS 36T, aluminum, BCD 104

BOTTOM BRACKET Shimano 83mm

PEDALS ---

CHAIN Shimano HG95, 10s

FRONT DERRAILLEUR E.13 LG1+ Race Carbon chain guide, IFD DMB (Direct mount Bashguard) Gen 2 Stealth Idler, Aluminum

hardware, adjustable/replaceable lower armature, polycarbonate, ISCG 05, adjustable upper slider

REAR DERRAILLEUR Shimano Saint RD-M820-SS, 10s, Shadow+, short cage

SHIFT LEVERS Shimano Saint SL-M820 10s, low friction multi bearing, instant release, multi release, 2-way release

CASSETTE Shimano CS-HG500-10, 11-25T, 10s

DERAILLEUR HANGER ---

OTHERS *Geometry kit included: +-1° / +-2° headset cups

WEIGHT ---