



Dimensions in metric (mm)

Copyright © Pole Bicycle Company Oy

Pole Bicycle Company Oy holds the right for changes

Disclaimer: This tool is only for educational purposes. Pole does not take any responsibility for wrongly typed information or programming errors.

| GRAVITYPLATFORM               |              |         |         |              |           |         |              |           |         |              |         |         |              |         |         |              |         |         |
|-------------------------------|--------------|---------|---------|--------------|-----------|---------|--------------|-----------|---------|--------------|---------|---------|--------------|---------|---------|--------------|---------|---------|
| DH / DOWNDURO 200             |              |         |         |              |           |         |              |           |         |              |         |         |              |         |         |              |         |         |
| FRAME SIZE                    | K1           |         |         | K2           |           |         | K3           |           |         | K1           |         |         | K2           |         |         | K3           |         |         |
| RIDER HEIGHT (CM)             | 155-167      | 157-170 | 160-173 | 169-181      | 171-184   | 174-187 | 183-195      | 185-198   | 188-201 | 157-169      | 159-172 | 162-175 | 171-184      | 173-186 | 176-189 | 185-198      | 187-200 | 190-203 |
| SIZE ADJUST                   | -5           | 0       | 10      | -5           | 0         | 10      | -5           | 0         | 10      | -5           | 0       | 10      | -5           | 0       | 10      | -5           | 0       | 10      |
| WHEELS                        | 29" / 27,5"  |         |         | 29" / 27,5"  |           |         | 29" / 27,5"  |           |         | 29" / 29"    |         |         | 29" / 29"    |         |         | 29" / 29"    |         |         |
| HEAD ANGLE                    | 63,5°        |         |         | 63,5°        |           |         | 63,5°        |           |         | 64,35°       |         |         | 64,35°       |         |         | 64,35°       |         |         |
| REACH ACTUAL                  | 428          | 433     | 443     | 458          | 463       | 473     | 488          | 493       | 503     | 439          | 444     | 454     | 469          | 474     | 484     | 499          | 504     | 514     |
| FRONT CENTER                  | 796          | 801     | 811     | 826          | 831       | 841     | 856          | 861       | 871     | 797          | 802     | 812     | 827          | 832     | 842     | 857          | 862     | 872     |
| CHAINSTAY LENGTH (EFFECTIVE)  | 448          |         |         | 448          |           |         | 448          |           |         | 448          |         |         | 448          |         |         | 448          |         |         |
| WHEELBASE                     | 1244         | 1249    | 1259    | 1274         | 1279      | 1289    | 1304         | 1309      | 1319    | 1245         | 1250    | 1260    | 1275         | 1280    | 1290    | 1305         | 1310    | 1320    |
| TOP TUBE                      | 549          | 554     | 564     | 579          | 584       | 594     | 609          | 614       | 624     | 558          | 563     | 573     | 588          | 593     | 603     | 618          | 623     | 633     |
| HEAD TUBE LENGTH              | 110          |         |         | 110          |           |         | 110          |           |         | 110          |         |         | 110          |         |         | 110          |         |         |
| STACK                         | 632          |         |         | 632          |           |         | 632          |           |         | 627          |         |         | 627          |         |         | 627          |         |         |
| SEAT TUBE LENGTH              | 343          |         |         | 343          |           |         | 350          |           |         | 343          |         |         | 343          |         |         | 350          |         |         |
| VERTICAL BB OFFSET FROM AXLES | -9           |         |         | -9           |           |         | -9           |           |         | 0            |         |         | 0            |         |         | 0            |         |         |
| BB GROUND GROUND DISTANCE     | 357          |         |         | 357          |           |         | 357          |           |         | 371          |         |         | 371          |         |         | 371          |         |         |
| SEAT TUBE ANGLE               | 79°          |         |         | 79°          |           |         | 79°          |           |         | 80°          |         |         | 80°          |         |         | 80°          |         |         |
| FORK OFFSET                   | 44-56        |         |         | 44-56        |           |         | 44-56        |           |         | 44-56        |         |         | 44-56        |         |         | 44-56        |         |         |
| LOWEST SEAT POST INSERTION    | 147 above BB |         |         | 147 above BB |           |         | 147 above BB |           |         | 147 above BB |         |         | 147 above BB |         |         | 147 above BB |         |         |
| SUSPENSION TRAVEL FRONT       | 200 (190)    |         |         | 200 (190)    |           |         | 200 (190)    |           |         | 200 (190)    |         |         | 200 (190)    |         |         | 200 (190)    |         |         |
| SUSPENSION TRAVEL REAR        | 200          |         |         | 200          |           |         | 200          |           |         | 200          |         |         | 200          |         |         | 200          |         |         |
| SHOCK SIZE                    | 75 x 250     |         |         | 75 x 250     |           |         | 75 x 250     |           |         | 75 x 250     |         |         | 75 x 250     |         |         | 75 x 250     |         |         |
| FORK AXLE TO CROWN            | 606          |         |         | 606          |           |         | 606          |           |         | 606          |         |         | 606          |         |         | 606          |         |         |
| ENDURO 180                    |              |         |         |              |           |         |              |           |         |              |         |         |              |         |         |              |         |         |
| FRAME SIZE                    | K1           |         |         | K2           |           |         | K3           |           |         | K1           |         |         | K2           |         |         | K3           |         |         |
| RIDER HEIGHT                  | 153-165      | 155-168 | 158-171 | 172-185      | 169 - 182 | 172-185 | 179-192      | 182 - 195 | 185-198 | 154-167      | 157-170 | 160-173 | 168-181      | 171-184 | 174-187 | 182-195      | 185-198 | 188-201 |
| SIZE ADJUST                   | -5           | 0       | 10      | -5           | 0         | 10      | -5           | 0         | 10      | -5           | 0       | 10      | -5           | 0       | 10      | -5           | 0       | 10      |
| WHEELS                        | 29" / 27,5"  |         |         | 29" / 27,5"  |           |         | 29" / 27,5"  |           |         | 29" / 29"    |         |         | 29" / 29"    |         |         | 29" / 29"    |         |         |
| HEAD ANGLE                    | 63,8°        |         |         | 63,8°        |           |         | 63,8°        |           |         | 64,6°        |         |         | 64,6°        |         |         | 64,6°        |         |         |
| REACH ACTUAL                  | 432          | 437     | 447     | 462          | 467       | 477     | 492          | 497       | 507     | 442          | 447     | 457     | 472          | 477     | 487     | 502          | 507     | 517     |
| FRONT CENTER                  | 786          | 791     | 801     | 816          | 821       | 831     | 846          | 851       | 861     | 786          | 791     | 801     | 816          | 821     | 831     | 846          | 851     | 861     |
| CHAINSTAY LENGTH (EFFECTIVE)  | 448          |         |         | 448          |           |         | 448          |           |         | 448          |         |         | 448          |         |         | 448          |         |         |
| WHEELBASE                     | 1234         | 1239    | 1249    | 1264         | 1269      | 1279    | 1294         | 1299      | 1309    | 1234         | 1239    | 1249    | 1264         | 1269    | 1279    | 1294         | 1299    | 1309    |
| TOP TUBE                      | 547          | 552     | 562     | 577          | 582       | 592     | 607          | 612       | 622     | 547          | 552     | 562     | 577          | 582     | 592     | 607          | 612     | 622     |
| HEAD TUBE LENGTH              | 110          |         |         | 110          |           |         | 110          |           |         | 110          |         |         | 110          |         |         | 110          |         |         |
| STACK                         | 625          |         |         | 625          |           |         | 625          |           |         | 627          |         |         | 627          |         |         | 627          |         |         |
| SEAT TUBE LENGTH              | 343          |         |         | 360          |           |         | 475          |           |         | 343          |         |         | 360          |         |         | 475          |         |         |
| VERTICAL BB OFFSET FROM AXLES | -14          |         |         | -14          |           |         | -14          |           |         | -2           |         |         | -2           |         |         | -2           |         |         |
| BB GROUND GROUND DISTANCE     | 356          |         |         | 356          |           |         | 356          |           |         | 368          |         |         | 368          |         |         | 368          |         |         |
| SEAT TUBE ANGLE               | 79°          |         |         | 79°          |           |         | 79°          |           |         | 80°          |         |         | 80°          |         |         | 80°          |         |         |
| FORK OFFSET                   | 44-51mm      |         |         | 44-51mm      |           |         | 44-51mm      |           |         | 44-51        |         |         | 44-51        |         |         | 44-51        |         |         |
| LOWEST SEAT POST INSERTION    | 147 ABOVE BB |         |         | 147 ABOVE BB |           |         | 147 ABOVE BB |           |         | 147 ABOVE BB |         |         | 147 ABOVE BB |         |         | 147 ABOVE BB |         |         |
| SUSPENSION TRAVEL FRONT       | 180          |         |         | 180          |           |         | 180          |           |         | 180          |         |         | 180          |         |         | 180          |         |         |
| SUSPENSION TRAVEL REAR        | 177          |         |         | 177          |           |         | 177          |           |         | 177          |         |         | 177          |         |         | 177          |         |         |
| SHOCK SIZE                    | 65 x 230     |         |         | 65 x 230     |           |         | 65 x 230     |           |         | 65 x 230     |         |         | 65 x 230     |         |         | 65 x 230     |         |         |
| FORK AXLE TO CROWN            | 586          |         |         | 586          |           |         | 586          |           |         | 586          |         |         | 586          |         |         | 586          |         |         |