

EPIC 8 EVO PRO



Satin Forest Green/Spruce/Metallic Spruce

The fastest downcountry bike in the world. Epic 8 EVO is the dressed up, cranked-to-11 expression of the new Epic 8. Spec'd to slay downcountry terrain with its unmatched combo of capability, efficiency, and light weight, Epic 8 EVO's updated kinematics allow for insanely efficient climbing—while the Ride Dynamics-tuned shock eats up rough terrain on the way down.

- The most capable 120mm bike on the planet. 12% more bump absorption and 20% less pedal bob
- Ride Dynamics tuned FOX Float Factory and 130mm FOX 34 Factory fork
- Roval Control carbon wheels excel everywhere from world cup xc races to your favorite weekend trail
- SRAM's legendary Code Silver Stealth 4-Piston brakes boast major stopping power with a sleek aesthetic
- Ride in confidence with super rugged and dependable XO Eagle AXS Transmission
- SWAT 4.0 in down tube to carry trail essentials

| EPIC 8 EVO PRO | S | M | L | XL |
|----------------------------------|------|------|------|------|
| Head Tube Angle (high) (degrees) | 65.9 | 65.9 | 65.9 | 65.9 |
| Trail (mm) | 120 | 120 | 120 | 120 |
| Chainstay Length (mm) | 435 | 435 | 435 | 435 |
| Seat Tube Angle (degrees) | 75.5 | 75 | 75 | 75 |
| Stack (mm) | 600 | 601 | 613 | 632 |
| BB Height (low) (mm) | 327 | 329 | 331 | 331 |
| Fork Length, Full (mm) | 540 | 540 | 540 | 540 |
| Reach (mm) | 415 | 445 | 470 | 495 |
| Top Tube Length, Horizontal (mm) | 569 | 605 | 633 | 662 |
| Wheelbase (mm) | 1151 | 1183 | 1214 | 1247 |
| BB Height (high) (mm) | 333 | 335 | 337 | 337 |
| Fork Rake/Offset (mm) | 44 | 44 | 44 | 44 |
| Bike Standover Height (mm) | 389 | 394 | 403 | 407 |
| Head Tube Length (mm) | 92 | 95 | 110 | 130 |
| BB Drop (low) (mm) | 43 | 41 | 39 | 39 |
| Front Center (mm) | 720 | 751 | 782 | 815 |
| Head Tube Angle (low) (degrees) | 65.4 | 65.4 | 65.4 | 65.4 |
| Seat Tube Length (mm) | 390 | 410 | 450 | 500 |
| Crank Length (mm) | 170 | 170 | 175 | 175 |
| Handlebar Width (mm) | 780 | 780 | 780 | 780 |
| Stem Length (mm) | 50 | 50 | 50 | 50 |
| Saddle Width (mm) | 155 | 143 | 143 | 143 |
| Seatpost Length (mm) | 125 | 150 | 175 | 175 |

| SPECS | Specifications subject to change without notice. |
|-----------------|---|
| FRAME | FACT 11m Carbon, Progressive XC Race Geometry, Rider-First Engineered™, SWAT downtube storage, threaded BB, 12x148mm UDH compatible rear dropout, internal cable routing, 120mm of travel |
| SWAT | SWAT internal downtube storage |
| REAR SHOCK | Fox Float Factory, Evol LV, Ride Dynamics Tuned, LSC/ Rebound adjust, 190x45mm |
| FORK | Fox 34 Factory, Grip2 Damper, 4 way adjust, 130mm travel, 44mm offset, 15x110mm |
| STEM | Raceface Turbine R, 50mm, 35mm clamp |
| HANDLEBARS | Roval Control Rise Carbon Handlebar, 780mm wide, 20mm rise, 35mm |
| GRIPS | Specialized Trail Grips |
| FRONT BRAKE | SRAM Code Silver Stealth, 4-piston caliper, hydraulic disc, 180/200mm rotor |
| REAR BRAKE | SRAM Code Silver Stealth, 4-piston caliper, hydraulic disc, 180mm rotor |
| REAR DERAILLEUR | SRAM XO Eagle Transmission |
| SHIFT LEVERS | SRAM AXS POD Controller |
| CASSETTE | SRAM XS 1295, 12 speed, 10-52 |
| CHAIN | Sram XO Eagle |
| CRANKSET | SRAM XO Eagle, DUB, 170/175mm, 32t |
| CHAINRINGS | Steel, 30T |
| BOTTOM BRACKET | SRAM DUB Threaded Wide |
| RIMS | Roval Control, Carbon offset design, 29mm internal width, 4mm hook width, Tubeless ready, 28h |
| FRONT HUB | Industry Nine 1/1, 6-bolt, 15mm Thru-axle, 110mm spacing, 28h |
| REAR HUB | Industry Nine 1/1, 12x148mm thru axle, XD freehub body, 28h |
| SPOKES | Stainless, 14g, black |
| FRONT TIRE | Specialized Purgatory, GRID Casing, T9 Compound, 29x2.4 |
| REAR TIRE | Specialized Ground Control, GRID Casing, T7 Compound, 29x2.35 |
| INNER TUBES | Standard, Presta Valve |
| SADDLE | Body Geometry Power Expert |
| SEATPOST | Fox Transfer Factory, 30.9, 1X remote, (SM:125mm, MD: 150mm, L-XL: 175mm) |
| SEAT BINDER | Specialized Alloy, 34.9, Steel bolt |
| Weight | 12.12kg (26 lb, 11.5 oz) |
| Weight Size | MD |

| PART NO. | DESCRIPTION | COLOR | SIZE |
|------------|------------------------------------|-----------------------------------|------|
| 90324-1102 | EPIC PRO EVO FSTGRN/SPR/METSPRS | Satin Forest Green/Spruce/Meta | S |
| 90324-1103 | | | M |
| 90324-1104 | | | L |
| 90324-1105 | | | XL |

EPIC 8 EVO COMP



SATIN BLUONYX DUNE WHITE

GLOSS PDRNDGO MIDNIGHT SHADOW

The fastest downcountry bike in the world. Epic 8 EVO is the dressed up, cranked-to-11 expression of the new Epic 8. Spec'd to slay downcountry terrain with its unmatched combo of capability, efficiency, and light weight, Epic 8 EVO's updated kinematics allow for insanely efficient climbing—while the Ride Dynamics-tuned shock eats up rough terrain on the way down.

- The most capable 120mm bike on the planet. 12% more bump absorption and 20% less pedal bob
- Ride Dynamics tuned FOX Float Performance and 130mm FOX 34 Performance fork
- Light weight and durable Specialized alloy wheels
- SRAM's legendary full-powered Code Bronze Stealth brakes make for a sleek cockpit and easy adjustments
- Reliable and durable GX Eagle 12-speed groupset
- SWAT 4.0 in down tube to carry trail essentials

| EPIC 8 EVO COMP | XS | S | M | L | XL |
|----------------------------------|------|------|------|------|------|
| Stack (mm) | 606 | 600 | 601 | 613 | 632 |
| Reach (mm) | 385 | 415 | 445 | 470 | 495 |
| Head Tube Length (mm) | 92 | 92 | 95 | 110 | 130 |
| Head Tube Angle (low) (degrees) | 65.4 | 65.4 | 65.4 | 65.4 | 65.4 |
| Head Tube Angle (high) (degrees) | 65.9 | 65.9 | 65.9 | 65.9 | 65.9 |
| BB Height (low) (mm) | 322 | 327 | 329 | 331 | 331 |
| BB Height (high) (mm) | 327 | 333 | 335 | 337 | 337 |
| BB Drop (low) (mm) | 49 | 43 | 41 | 39 | 39 |
| Trail (mm) | 120 | 120 | 120 | 120 | 120 |
| Fork Length, Full (mm) | 540 | 540 | 540 | 540 | 540 |
| Fork Rake/Offset (mm) | 44 | 44 | 44 | 44 | 44 |
| Front Center (mm) | 690 | 720 | 751 | 782 | 815 |
| Chainstay Length (mm) | 435 | 435 | 435 | 435 | 435 |
| Wheelbase (mm) | 1121 | 1151 | 1183 | 1214 | 1247 |
| Bike Standover Height (mm) | 382 | 389 | 394 | 403 | 407 |
| Seat Tube Length (mm) | 370 | 390 | 410 | 450 | 500 |
| Seat Tube Angle (degrees) | 76 | 75.5 | 75 | 75 | 75 |
| Top Tube Length, Horizontal (mm) | 535 | 569 | 605 | 633 | 662 |
| Crank Length (mm) | 165 | 170 | 170 | 175 | 175 |
| Handlebar Width (mm) | 760 | 760 | 760 | 760 | 760 |
| Stem Length (mm) | 50 | 50 | 50 | 50 | 50 |
| Saddle Width (mm) | 155 | 155 | 143 | 143 | 143 |
| Seatpost Length (mm) | 125 | 125 | 150 | 170 | 170 |

SPECS

Specifications subject to change without notice.

| | |
|-----------------|---|
| FRAME | FACT 11m Carbon, Progressive XC Race Geometry, Rider-First Engineered™, SWAT downtube storage, threaded BB, 12x148mm UDH compatible rear dropout, internal cable routing, 120mm of travel |
| SWAT | SWAT internal downtube storage |
| REAR SHOCK | Fox Float Performance, Evol LV, Ride Dynamics Tuned, 2-position compression adjust, 190x45mm |
| FORK | Fox 34 Performance, Grip Damper, Compression adjust, 130mm travel, 44mm offset, 15x110mm |
| STEM | Alloy Stem, 35mm clamp, 60mm |
| SADDLE | Body Geometry Power Sport, steel rails |
| HANDLEBARS | Specialized Alloy, 20mm rise, 35mm, 760mm wide |
| GRIPS | Specialized Trail Grips |
| FRONT BRAKE | SRAM Code Bronze Stealth, 4-piston caliper, hydraulic disc, 180/200mm rotor |
| REAR BRAKE | SRAM Code Bronze Stealth, 4-piston caliper, hydraulic disc, 180mm rotor |
| REAR DERAILLEUR | SRAM GX Eagle, 12-speed |
| SHIFT LEVERS | SRAM GX, trigger, 12-speed |
| CASSETTE | SRAM XG-1275, 12-speed, 10-52t |
| CHAIN | SRAM NX Eagle, 12-speed |
| CRANKSET | SRAM X1000 Eagle, DUB, 165/170/175mm 32T |
| CHAINRINGS | Steel 32T |
| BOTTOM BRACKET | SRAM DUB, BSA 73mm, Threaded |
| RIMS | Specialized Alloy 29, 30mm internal width, tubeless |
| FRONT HUB | Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h |
| REAR HUB | Alloy, sealed cartridge bearings, 148mmx12mm thru-axle, 28h |
| SPOKES | DT Swiss Industry |
| FRONT TIRE | Specialized Purgatory, GRID Casing, T9 Compound, 29x2.4 |
| REAR TIRE | Specialized Ground Control, GRID Casing, T7 Compound, 29x2.35 |
| INNER TUBES | Standard, Presta Valve |
| SEATPOST | X-Fusion Manic, 30.9, 125/150 Travel, 0mm offset |
| SEAT BINDER | Specialized Alloy, 34.9, Steel bolt |
| Weight | 12.61kg (27 lb, 12.8 oz) |
| Weight Size | MD |

| PART NO. | DESCRIPTION | COLOR | SIZE |
|------------|-------------------------------------|----------------------------------|------|
| 90324-5201 | EPIC COMP EVO PDRNDGO/MNSHDW XS | GLOSS PDRNDGO MIDNIGHT SHADOW | XS |
| 90324-5202 | | | S |
| 90324-5203 | | | M |
| 90324-5204 | | | L |
| 90324-5205 | | | XL |
| 90324-5301 | EPIC COMP EVO BLUONYX/DUNEWHT XS | SATIN BLUONYX DUNE WHITE | XS |
| 90324-5302 | | | S |
| 90324-5303 | | | M |
| 90324-5304 | | | L |
| 90324-5305 | | | XL |

EPIC 8 EVO PRO FRAMESET



Satin White Fog Tint/Smoke

The fastest downcountry bike in the world. Epic 8 EVO is the dressed up, cranked-to-11 expression of the new Epic 8. Spec'd to slay downcountry terrain with its unmatched combo of capability, efficiency, and light weight, Epic 8 EVO's updated kinematics allow for insanely efficient climbing—while the Ride Dynamics-tuned shock eats up rough terrain on the way down.

- FACT 11m Carbon
- Progressive XC geometry
- SWAT 4.0 in downtube to carry trail essentials
- Ride Dynamics tuned FOX Float Factory

| SPECS | Specifications subject to change without notice. |
|--------------|---|
| FRAME | FACT 11m Carbon, Progressive XC Race Geometry, Rider-First Engineered™, SWAT downtube storage, threaded BB, 12x148mm UDH compatible rear dropout, internal cable routing, 120mm of travel |
| SWAT | SWAT internal downtube storage |
| REAR SHOCK | Fox Float Factory, Evol LV, Ride Dynamics Tuned, LSC/ Rebound adjust, 190x45mm |
| SEAT BINDER | Specialized Alloy 34.9, Titanium Bolt |
| Weight | 2.21kg (4 lb, 14 oz) |
| Weight Size | MD |

| EPIC 8 EVO PRO FRAMESET | XS | S | M | L | XL |
|----------------------------------|-----------|----------|----------|----------|-----------|
| Stack (mm) | 606 | 600 | 601 | 613 | 632 |
| Reach (mm) | 385 | 415 | 445 | 470 | 495 |
| Head Tube Length (mm) | 92 | 92 | 95 | 110 | 130 |
| Head Tube Angle (low) (degrees) | 65.4 | 65.4 | 65.4 | 65.4 | 65.4 |
| Head Tube Angle (high) (degrees) | 65.9 | 65.9 | 65.9 | 65.9 | 65.9 |
| BB Height (low) (mm) | 322 | 327 | 329 | 331 | 331 |
| BB Height (high) (mm) | 327 | 333 | 335 | 337 | 337 |
| BB Drop (low) (mm) | 49 | 43 | 41 | 39 | 39 |
| Trail (mm) | 120 | 120 | 120 | 120 | 120 |
| Fork Length, Full (mm) | 540 | 540 | 540 | 540 | 540 |
| Fork Rake/Offset (mm) | 44 | 44 | 44 | 44 | 44 |
| Front Center (mm) | 690 | 720 | 751 | 782 | 815 |
| Chainstay Length (mm) | 435 | 435 | 435 | 435 | 435 |
| Wheelbase (mm) | 1121 | 1151 | 1183 | 1214 | 1247 |
| Bike Standover Height (mm) | 382 | 389 | 394 | 403 | 407 |
| Seat Tube Length (mm) | 370 | 390 | 410 | 450 | 500 |
| Seat Tube Angle (degrees) | 76 | 75.5 | 75 | 75 | 75 |
| Top Tube Length, Horizontal (mm) | 535 | 569 | 605 | 633 | 662 |

| PART NO. | DESCRIPTION | COLOR | SIZE |
|-----------------|---------------------------------------|----------------------------|-------------|
| 70324-1001 | EPIC PRO EVO FRM WHT/FOGTNT/SMK XS | Satin White Fog Tint/Smoke | XS |
| 70324-1002 | | | S |
| 70324-1003 | | | M |
| 70324-1004 | | | L |
| 70324-1005 | | | XL |