

# S-WORKS EPIC 8



Gloss Carbon/Metallic Vivid Pink/Viavi Magenta Gold/Metallic Midnight Shadow

Gloss Carbon/Astral Blue/Electric Green/Cyan Edge Fade/Metallic White Silver

The all-new Epic 8 evolves the formula of fastest through capability, efficiency, and lightweight integration. Modern XC tracks demand more and more capability by the day. Enter Epic 8. Its improved kinematics make it the most efficient pedaling bike we've ever tested, while custom valved (and tuned) shocks soak up every bump. It's a wolf in wolf's clothing.

- The most capable 120mm bike on the planet. 12% more bump absorption and 20% less pedal bob
- Ride Dynamics developed RockShox SIDLuxe ULTIMATE shock and tuned SID ULTIMATE fork w/ Flight Attendant
- Custom tuned shock features 3 unique damper settings
- Specialized Ride Dynamics-Tuned RockShox Flight Attendant collects real-time data from you and the terrain to determine optimal compression settings.
- Obscenely light, smooth riding, and extra durable Roval Control SL wheels
- Sleek and lightweight Roval Control SL integrated cockpit
- Top tier Level Ultimate Stealth 4-Piston brakes provide superior power to weight stopping performance
- SRAM XX SL T-Type AXS Transmission provides the pinnacle of cross-country shifting performance
- SWAT 4.0 in down tube to carry trail essentials

S-WORKS EPIC 8	S	M	L	XL
Front Center (mm)	716	747	778	811
Seat Tube Length (mm)	390	410	450	500
Stack (mm)	597	598	610	628
Head Tube Angle (high) (degrees)	66.4	66.4	66.4	66.4
Trail (mm)	117	117	117	117
Chainstay Length (mm)	435	435	435	435
Reach (low) (mm)	420	450	475	500
Seat Tube Angle (degrees)	76	75.5	75.5	75.5
BB Height (low) (mm)	324	326	328	328
Fork Length, Full (mm)	530	530	530	530
Head Tube Length (mm)	92	95	110	130
Top Tube Length, Horizontal (mm)	569	605	633	662
Wheelbase (mm)	1147	1179	1210	1243
BB Height (high) (mm)	329	331	333	333
Fork Rake/Offset (mm)	44	44	44	44
Bike Standover Height (mm)	383	388	397	402
BB Drop (low) (mm)	46	44	42	42
Head Tube Angle (low) (degrees)	65.9	65.9	65.9	65.9
Crank Length (mm)	170	170	175	175
Handlebar Width (mm)	760	760	760	760
Stem Length (mm)	60	60	60	60
Saddle Width (mm)	155	143	143	143
Seatpost Length (mm)	125	125	150	170

## SPECS

### Specifications subject to change without notice.

FRAME	S-Works FACT 12m Carbon, Progressive XC Race Geometry, Rider-First Engineered™, SWAT downtube storage, threaded BB, 12x148mm UDH compatible rear dropout, internal cable routing, 120mm of travel, Optimized for wireless drivetrain and seatpost
SWAT	SWAT internal downtube storage
REAR SHOCK	RockShox SIDLuxe ULTIMATE Flight Attendant, Ride Dynamics developed 3 position, Solo Air, 190x45mm
FORK	RockShox SID ULTIMATE Flight Attendant, Ride Dynamics developed 3 position, Debon Air, 15x110mm, 44mm offset, 120mm Travel
SADDLE	Body Geometry S-Works Power, carbon fiber rails, carbon fiber base
HANDLEBARS	Roval Control SL Integrated cockpit, 60mm X- 12 degree integrated stem, 8-degree backsweep, 1 degree upsweep, 760mm wide
GRIPS	Specialized Trail Grips
FRONT BRAKE	SRAM Level Ultimate Stealth, 4-piston caliper, hydraulic disc, 160/180mm rotor
REAR BRAKE	SRAM Level Ultimate Stealth, 4-piston caliper, hydraulic disc, 160mm rotor
REAR DERAILLEUR	SRAM XX SL Eagle AXS
SHIFT LEVERS	SRAM AXS POD Ultimate Controller
CASSETTE	SRAM XX Eagle SL 10-52t
CHAIN	SRAM XX SL Eagle
CRANKSET	SRAM XX SL Eagle Power Meter Crankset, 170mm/175mm
CHAINRINGS	34T
BOTTOM BRACKET	SRAM DUB, BSA 73mm, Threaded
RIMS	Roval Control SL, Carbon offset design, 29mm internal width, 4mm hook width, Tubeless ready, 24h
FRONT HUB	Roval Control SL, DT Swiss Internals, Ceramic Bearings, 6-bolt, 15mm thru-axle, 110mm spacing, Torque caps, 24h straight pull
REAR HUB	Roval Control SL, DT Swiss 180 Internals, DT Swiss Ratchet EXP, Ceramic bearings, 12mm thru-axle, 148mm spacing, 24h straight-pull
SPOKES	DT Swiss Aerolite T-head
FRONT TIRE	Specialized Fast Trak, Control Casing, T7 Compound, 29x2.35
REAR TIRE	Specialized Renegade, Control Casing, T5 Compound, 29x2.35
INNER TUBES	Specialized Turbo Tube
SEATPOST	RockShox Reverb AXS, 30.9mm, S: 125, M:150, L/XL: 170mm
SEAT BINDER	Specialized Alloy 34.9, Titanium Bolt
Weight	10.24kg (22 lb, 9.2 oz)
Weight Size	MD

PART NO.	DESCRIPTION	COLOR	SIZE
90324-0102	EPIC SW CARB/ASTRLBLU/EGRN S	Gloss Carbon/Astral Blue/Elect	S
90324-0103			M
90324-0104			L
90324-0105			XL
90324-0002	EPIC SW CARB/VIVPNKMET/MNSHDWMET S	Gloss Carbon/Metallic Vivid Pi	S
90324-0003			M

## S-WORKS EPIC 8

---

<b>PART NO.</b>	<b>DESCRIPTION</b>	<b>COLOR</b>	<b>SIZE</b>
90324-0004	EPIC SW CARB/VIVPNKMET/ MNSHDWMET L	Gloss Carbon/Metallic Vivid Pi	L
90324-0005			XL



Satin Carbon/Metallic Sapphire/Metallic White Silver

The all-new Epic 8 evolves the formula of fastest through capability, efficiency, and lightweight integration. Modern XC tracks demand more and more capability by the day. Enter Epic 8. Its improved kinematics make it the most efficient pedaling bike we've ever tested, while custom valved (and tuned) shocks soak up every bump. It's a wolf in wolf's clothing.

- The most capable 120mm bike on the planet. 12% more bump absorption and 20% less pedal bob
- Ride Dynamics developed RockShox SIDLuxe ULTIMATE shock and SID ULTIMATE fork
- Custom tuned shock features 3 unique damper settings
- Roval Control carbon wheels excel everywhere from world cup xc races to your favorite weekend trail
- Data-ready with Quarq Spindle power meter
- SRAM Level Silver 4-Piston brakes bring trail bike stopping power in a light XC race weight class
- Ride in confidence with super rugged and dependable XO Eagle AXS Transmission
- SWAT 4.0 in down tube to carry trail essentials

EPIC 8 PRO	S	M	L	XL
Front Center (mm)	716	747	778	811
Seat Tube Length (mm)	390	410	450	500
Stack (mm)	597	598	610	628
Head Tube Angle (high) (degrees)	66.4	66.4	66.4	66.4
Trail (mm)	117	117	117	117
Chainstay Length (mm)	435	435	435	435
Reach (low) (mm)	420	450	475	500
Seat Tube Angle (degrees)	76	75.5	75.5	75.5
BB Height (low) (mm)	324	326	328	328
Fork Length, Full (mm)	530	530	530	530
Head Tube Length (mm)	92	95	110	130
Top Tube Length, Horizontal (mm)	569	605	633	662
Wheelbase (mm)	1147	1179	1210	1243
BB Height (high) (mm)	329	331	333	333
Fork Rake/Offset (mm)	44	44	44	44
Bike Standover Height (mm)	383	388	397	402
BB Drop (low) (mm)	46	44	42	42
Head Tube Angle (low) (degrees)	65.9	65.9	65.9	65.9
Crank Length (mm)	170	170	175	175
Handlebar Width (mm)	760	760	760	760
Stem Length (mm)	60	60	60	60
Saddle Width (mm)	155	143	143	143
Seatpost Length (mm)	100	125	125	125

## SPECS

## Specifications subject to change without notice.

FRAME	FACT 11m Carbon, Progressive XC Race Geometry, Rider-First Engineered™, SWAT downtube storage, threaded BB, 12x148mm UDH compatible rear dropout, internal cable routing, 120mm of travel
SWAT	SWAT internal downtube storage
REAR SHOCK	RockShox SIDLuxe ULTIMATE, Ride Dynamics developed 3 position, TwistLoc remote adjust, Solo Air, 190x45mm
FORK	RockShox SID ULTIMATE, Ride Dynamics developed 3 position, TwistLoc remote adjust, Debon Air, 15x110mm, 44mm offset, 120mm Travel
STEM	Specialized Pro SL, alloy, 4-bolt
HANDLEBARS	S-Works Carbon XC Mini Rise, 6-degree upsweep, 8-degree backsweep, 10mm rise, 760mm, 31.8mm
GRIPS	SRAM Slip on with Twist-Loc
FRONT BRAKE	SRAM Level Silver, 4-piston caliper, hydraulic disc, stealth, 160/180mm rotor
REAR BRAKE	SRAM Level Silver, 4-piston caliper, hydraulic disc, stealth, 160 rotor
REAR DERAILLEUR	SRAM XO Eagle Transmission
SHIFT LEVERS	SRAM AXS POD Controller
CASSETTE	SRAM XS 1295, 12 speed, 10-52
CHAIN	SRAM XO Eagle
CRANKSET	SRAM XO Eagle, Quarq Spindle power meter, DUB, 170/175mm, 34t
CHAINRINGS	Alloy 34t
BOTTOM BRACKET	SRAM DUB Threaded Wide
RIMS	Roval Control, Carbon offset design, 29mm internal width, 4mm hook width, Tubeless ready, 28h
FRONT HUB	DT Swiss 350, 6-bolt, 15mm Thru-axle, 110mm spacing, 28h straight-pull
REAR HUB	DT Swiss 350 straight-pull, 6-bolt, DT Swiss Ratchet, 12x148mm thru axle, XD freehub body, 28h straight-pull
SPOKES	DT Swiss Comp Race
FRONT TIRE	Specialized Fast Trak, Control Casing, T7 Compound, 29x2.35
REAR TIRE	Specialized Renegade, Control Casing, T5 Compound, 29x2.35
INNER TUBES	Specialized Turbo Tube
SEATPOST	Bike Yoke Divine SL, 30.9mm, SM: 100/ MD-XL: 125mm,
SADDLE	Body Geometry Power Expert
SEAT BINDER	Specialized Alloy, 34.9, Steel bolt
Weight	10.87kg (23 lb, 15.4 oz)
Weight Size	MD

PART NO.	DESCRIPTION	COLOR	SIZE
90324-1002	EPIC PRO CARB/METSPHR/METWHTSIL S	Satin Carbon/Metallic Sapphire	S
90324-1003			M
90324-1004			L
90324-1005			XL



GLOSS CARB BLACK PEARL WHT



SATIN REDSKY WHT

The all-new Epic 8 evolves the formula of fastest through capability, efficiency, and lightweight integration. Modern XC tracks demand more and more capability by the day. Enter Epic 8. Its improved kinematics make it the most efficient pedaling bike we've ever tested, while custom valved (and tuned) shocks soak up every bump. It's a wolf in wolf's clothing.

- The most capable 120mm bike on the planet. 12% more bump absorption and 20% less pedal bob
- Ride Dynamics developed SIDLuxe Select+ shock and SID Select+ fork
- Custom tuned shock features 3 unique damper settings
- Roval Control carbon wheels excel everywhere from world cup xc races to your favorite weekend trail
- SRAM Level Bronze Stealth 4-Piston brakes feature trail-ready stopping power in a race-ready system
- No-compromise GX Eagle AXS Transmission provides smooth shifting all day, specially under load
- SWAT 4.0 in down tube to carry trail essentials

EPIC 8 EXPERT	XS	S	M	L	XL
Head Tube Angle (high) (degrees)	66.4	66.4	66.4	66.4	66.4
Stack (mm)	603	597	598	610	628
Trail (mm)	117	117	117	117	117
Chainstay Length (mm)	435	435	435	435	435
Seat Tube Angle (degrees)	76.5	76	75.5	75.5	75.5
BB Height (low) (mm)	318	324	326	328	328
Fork Length, Full (mm)	530	530	530	530	530
Reach (low) (mm)	390	420	450	475	500
Top Tube Length, Horizontal (mm)	535	569	605	633	662
Wheelbase (mm)	1117	1147	1179	1210	1243
BB Height (high) (mm)	323	329	331	333	333
Fork Rake/Offset (mm)	44	44	44	44	44
Head Tube Length (mm)	92	92	95	110	130
Bike Standover Height (mm)	376	383	388	397	402
BB Drop (low) (mm)	52	46	44	42	42
Front Center (mm)	687	716	747	778	811
Head Tube Angle (low) (degrees)	65.9	65.9	65.9	65.9	65.9
Seat Tube Length (mm)	370	390	410	450	500
Crank Length (mm)	165	170	170	175	175
Handlebar Width (mm)	750	750	750	750	750
Stem Length (mm)	60	60	60	60	60
Saddle Width (mm)	155	155	143	143	143
Seatpost Length (mm)	100	125	125	150	170

## SPECS

## Specifications subject to change without notice.

FRAME	FACT 11m Carbon, Progressive XC Race Geometry, Rider-First Engineered™, SWAT downtube storage, threaded BB, 12x148mm UDH compatible rear dropout, internal cable routing, 120mm of travel
SWAT	SWAT internal downtube storage
REAR SHOCK	RockShox SIDLuxe Select+, Ride Dynamics developed 3 position, TwistLoc remote adjust, Solo Air, 190x45mm
HANDLEBARS	Specialized Alloy Minirise, 10mm rise, 750mm, 31.8mm clamp
FORK	RockShox SID Select+, Ride Dynamics developed 3 position, TwistLoc remote adjust, Debon Air, 15x110mm, 44mm offset, 120mm Travel
STEM	Specialized XC, 3D-forged alloy, 4-bolt, 6-degree rise
SADDLE	Body Geometry Power Sport, steel rails
GRIPS	SRAM Slip on with Twist-Loc
FRONT BRAKE	SRAM Level Bronze Stealth, 4-piston caliper, hydraulic disc, 160/180mm rotor
REAR BRAKE	SRAM Level Bronze Stealth, 4-piston caliper, hydraulic disc, 160mm rotor
REAR DERAILLEUR	SRAM GX Eagle AXS Transmission
SHIFT LEVERS	SRAM AXS POD Controller
CASSETTE	SRAM XS 1275, 12-speed, 10-52t
CHAIN	SRAM GX Eagle T-Type chain
CRANKSET	SRAM GX Eagle, DUB, 165/170/175mm
CHAINRINGS	Steel, 34T
BOTTOM BRACKET	SRAM DUB Threaded Wide
RIMS	Roval Control, Carbon offset design, 29mm internal width, 4mm hook width, Tubeless ready, 28h
FRONT HUB	DT Swiss 350, 6-bolt, 15mm Thru-axle, 110mm spacing, 28h straight-pull
REAR HUB	DT Swiss 350 straight-pull, 6-bolt, DT Swiss Ratchet, 12x148mm thru axle, XD freehub body, 28h straight-pull
SPOKES	DT Swiss Comp Race
FRONT TIRE	Specialized Fast Trak, Control Casing, T7 Compound, 29x2.35
REAR TIRE	Specialized Renegade, Control Casing, T5 Compound, 29x2.35
INNER TUBES	Standard, Presta Valve
SEATPOST	X-Fusion Manic, 30.9, 100/125/150mm travel
SEAT BINDER	Specialized Alloy, 34.9, Steel bolt
Weight	11.10kg (24 lb, 7.5 oz)
Weight Size	MD

PART NO.	DESCRIPTION	COLOR	SIZE
90324-3101	EPIC EXPERT CARB/BLKPRL/WHT XS	GLOSS CARB BLACK PEARL WHT	XS
90324-3102			S
90324-3103			M
90324-3104			L
90324-3105			XL
90324-3001	EPIC EXPERT REDSKY/WHT XS	SATIN REDSKY WHT	XS
90324-3002			S

## EPIC 8 EXPERT

---

<b>PART NO.</b>	<b>DESCRIPTION</b>	<b>COLOR</b>	<b>SIZE</b>
90324-3003	EPIC EXPERT REDSKY/WHT M	SATIN REDSKY WHT	M
90324-3004			L
90324-3005			XL



GLOSS DUNE WHITE SMK



SATIN METSPHR WHT

The all-new Epic 8 evolves the formula of fastest through capability, efficiency, and lightweight integration. Modern XC tracks demand more and more capability by the day. Enter Epic 8. Its improved kinematics make it the most efficient pedaling bike we've ever tested, while custom valved (and tuned) shocks soak up every bump. It's a wolf in wolf's clothing.

- The most capable 120mm bike on the planet. 12% more bump absorption and 20% less pedal bob
- SRAM Level Bronze Stealth 4-Piston brakes feature trail-ready stopping power in a race-ready system
- Reliable and durable GX Eagle 12-speed groupset
- Light weight and durable Specialized alloy wheels
- Ride Dynamics developed RockShox SIDLuxe Select+ shock and SID Select fork
- Custom tuned shock features 3 unique damper settings
- SWAT 4.0 in down tube to carry trail essentials

EPIC 8 COMP	XS	S	M	L	XL
Head Tube Angle (high) (degrees)	66.4	66.4	66.4	66.4	66.4
Stack (mm)	603	597	598	610	628
Trail (mm)	117	117	117	117	117
Chainstay Length (mm)	435	435	435	435	435
Seat Tube Angle (degrees)	76.5	76	75.5	75.5	75.5
BB Height (low) (mm)	318	324	326	328	328
Fork Length, Full (mm)	530	530	530	530	530
Reach (low) (mm)	390	420	450	475	500
Top Tube Length, Horizontal (mm)	535	569	605	633	662
Wheelbase (mm)	1117	1147	1179	1210	1243
BB Height (high) (mm)	323	329	331	333	333
Fork Rake/Offset (mm)	44	44	44	44	44
Head Tube Length (mm)	92	92	95	110	130
Bike Standover Height (mm)	376	383	388	397	402
BB Drop (low) (mm)	52	46	44	42	42
Front Center (mm)	687	716	747	778	811
Head Tube Angle (low) (degrees)	65.9	65.9	65.9	65.9	65.9
Seat Tube Length (mm)	370	390	410	450	500
Crank Length (mm)	165	170	170	175	175
Handlebar Width (mm)	750	750	750	750	750
Stem Length (mm)	60	60	60	60	60
Saddle Width (mm)	155	155	143	143	143
Seatpost Length (mm)	100	125	125	150	170

## SPECS

## Specifications subject to change without notice.

FRAME	FACT 11m Carbon, Progressive XC Race Geometry, Rider-First Engineered™, SWAT downtube storage, threaded BB, 12x148mm UDH compatible rear dropout, internal cable routing, 120mm of travel
SWAT	SWAT internal downtube storage
REAR SHOCK	RockShox SIDLuxe Select+, Ride Dynamics developed 3 position, TwistLoc remote adjust, Solo Air, 190x45mm
HANDLEBARS	Specialized Alloy Minirise, 10mm rise, 750mm, 31.8mm clamp
FORK	RockShox SID Select, Ride Dynamics developed 3 position, TwistLoc remote adjust, Debon Air, 15x110mm, 44mm offset, 120mm Travel
STEM	Specialized, 3D-forged alloy, 4-bolt, 7-degree rise
SADDLE	Body Geometry Power Sport, steel rails
GRIPS	SRAM Slip on with Twist-Loc
FRONT BRAKE	SRAM Level Bronze Stealth, 4-piston caliper, hydraulic disc, 160/180mm rotor
REAR BRAKE	SRAM Level Bronze Stealth, 4-piston caliper, hydraulic disc, 160mm rotor
REAR DERAILLEUR	SRAM GX Eagle, 12-speed
SHIFT LEVERS	SRAM GX, trigger, 12-speed
CASSETTE	SRAM XG-1275, 12-speed, 10-52t
CHAIN	SRAM NX Eagle, 12-speed
CRANKSET	SRAM X1000 Eagle, DUB, 170/175mm
CHAINRINGS	Steel, 32T
BOTTOM BRACKET	SRAM DUB, BSA 73mm, Threaded
RIMS	Specialized Alloy 29, 28mm internal width, tubeless
FRONT HUB	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
REAR HUB	Alloy, sealed cartridge bearings, 148mmx12mm thru-axle, 28h
SPOKES	DT Swiss Industry
FRONT TIRE	Specialized Fast Trak, Control Casing, T7 Compound, 29x2.35
REAR TIRE	Specialized Renegade, Control Casing, T5 Compound, 29x2.35
INNER TUBES	Standard, Presta Valve
SEATPOST	X-Fusion Manic, 30.9, 125/150 Travel, 0mm offset
SEAT BINDER	Specialized Alloy, 34.9, Steel bolt
Weight	11.7kg (25 lb, 12.7 oz)
Weight Size	MD

PART NO.	DESCRIPTION	COLOR	SIZE
90324-5001	EPIC COMP DUNEWHT/SMK XS	GLOSS DUNE WHITE SMK	XS
90324-5002			S
90324-5003			M
90324-5004			L
90324-5005			XL
90324-5101	EPIC COMP METSPHR/WHT XS	SATIN METSPHR WHT	XS
90324-5102			S
90324-5103			M
90324-5104			L

## EPIC 8 COMP

---

<b>PART NO.</b>	<b>DESCRIPTION</b>	<b>COLOR</b>	<b>SIZE</b>
90324-5105	EPIC COMP METSPHR/WHT XL	SATIN METSPHR WHT	XL

---

# S-WORKS EPIC 8 FRAMESET



Gloss Astral Blue/Metallic Sapphire/Black



Gloss Carbon/Metallic Vivid Pink/Viavi Magenta Gold/Metallic Midnight Shadow



Satin Carbon/Metallic White Silver

The all-new Epic 8 evolves the formula of fastest through capability, efficiency, and lightweight integration. Modern XC tracks demand more and more capability by the day. Enter Epic 8. Its improved kinematics make it the most efficient pedaling bike we've ever tested, while custom valved (and tuned) shocks soak up every bump. It's a wolf in wolf's clothing.

- Ride Dynamics developed RockShox SIDLuxe ULTIMATE shock and SID ULTIMATE fork
- Custom tuned shock features 3 unique damper settings
- Light weight and stiff Roval Control SL carbon seatpost
- SWAT 4.0 in downtube to carry trail essentials

## SPECS

## Specifications subject to change without notice.

FRAME	S-Works FACT 12m Carbon, Progressive XC Race Geometry, Rider-First Engineered™, SWAT downtube storage, threaded BB, 12x148mm UDH compatible rear dropout, internal cable routing, 120mm of travel, Optimized for wireless drivetrain and seatpost
SWAT	SWAT internal downtube storage
REAR SHOCK	RockShox SIDLuxe ULTIMATE, Ride Dynamics developed 3 position, TwistLoc remote adjust, Solo Air, 190x45mm
FORK	RockShox SID ULTIMATE, Ride Dynamics developed 3 position, TwistLoc remote adjust, Debon Air, 15x110mm, 44mm offset, 120mm Travel
GRIPS	SRAM Slip on with Twist-Loc
SEATPOST	Roval Control SL carbon seatpost, Two-bolt clamp, 0mm offset, 415/370mm x 30.9
SEAT BINDER	Specialized Alloy 34.9, Titanium Bolt
Weight	3.6kg (7 lb, 15 oz)
Weight Size	MD

S-WORKS EPIC 8 FRAMESET	S	M	L	XL
Front Center (mm)	716	747	778	811
Seat Tube Length (mm)	390	410	450	500
Stack (mm)	597	598	610	628
Head Tube Angle (high) (degrees)	66.4	66.4	66.4	66.4
Trail (mm)	117	117	117	117
Chainstay Length (mm)	435	435	435	435
Reach (low) (mm)	420	450	475	500
Seat Tube Angle (degrees)	76	75.5	75.5	75.5
BB Height (low) (mm)	324	326	328	328
Fork Length, Full (mm)	530	530	530	530
Head Tube Length (mm)	92	95	110	130
Top Tube Length, Horizontal (mm)	569	605	633	662
Wheelbase (mm)	1147	1179	1210	1243
BB Height (high) (mm)	329	331	333	333
Fork Rake/Offset (mm)	44	44	44	44
Bike Standover Height (mm)	383	388	397	402
BB Drop (low) (mm)	46	44	42	42
Head Tube Angle (low) (degrees)	65.9	65.9	65.9	65.9
Seatpost Length (mm)	370	370	415	415

PART NO.	DESCRIPTION	COLOR	SIZE
70324-0102	EPIC SW FRMSET ASTRLBLU/PDRNDGO/BLK S	Gloss Astral Blue/Metallic Sap	S
70324-0103			M
70324-0104			L
70324-0105			XL
70324-0002	EPIC SW FRMSET CARB/VIV PNKMET/MNSHDWMET S	Gloss Carbon/Metallic Vivid Pi	S
70324-0003			M
70324-0004			L
70324-0005			XL
70324-0202	EPIC SW FRMSET CARB/METWHTSIL S	Satin Carbon/Metallic White Si	S
70324-0203			M
70324-0204			L
70324-0205			XL