



IZZO 29 CORE 3 CF

FRAME	Ultra Modulus Carbon Frame	V4LR 130 mm 148 x 12 mm YT Thru Axle UDH
EXT STORAGE	CRANKBROTHERS	S.O.S TS2 Tube Stash OE
FORK	ÖHLINS RXF36 M. 3	29" 140 mm H/LSC LSR 15x110 mm 51 mm Offset
SHOCK	ÖHLINS TTX1 Air	210 x 55 mm H/LSC LSR C30R40 (S-L) C30R60 (XL-XXL)
HEADSET	ACROS AZX	579 Block Lock (S-M) 579 (L-XXL) 2 Spacer 5 mm
STEM	RENTHAL Apex 35	50 mm +/-6° Black/Black
HANDLEBAR	RENTHAL Fatbar 35 AL	780 mm 7° Back 5° Up 20 mm Rise Custom Black
GRIPS	ODI ELITE MOTION V2.1	Lock-On
CRANKSET	SHIMANO SLX FC-M7120	170 mm 32T Hollowtech 2
CASSETTE	SHIMANO SLX CS-M7100	10-51T 12-Speed Hyperglide+
DERAILLEUR	SHIMANO SLX RD-M7100	12-Speed Shadow+
SHIFTER REAR	SHIMANO XT SL-M8100	12-Speed Rapidfire Plus 2-Way-Release
WHEELSET	DT SWISS XM1700	29" 30 mm 110 x 15 mm 6-Bolt
TIRE FRONT	MAXXIS Minion DHR II	29" 30 mm 148 x 12 mm 350 Ratchet 36 SL 6-Bolt MS
TIRE REAR	MAXXIS Minion DHR II	29" x 2.4 WT 3C MaxxTerra EXO TR
BRAKES	SHIMANO SLX	29" x 2.4 WT 3C MaxxTerra EXO+ TR
SEATPOST	YT POSTMAN V2	Rotor SM-RT66 203 mm / 180 mm 6-Bolt
	SHIMANO SL-MT500	Ø 31.6 mm Adjustable drop 20 / 10 / 5 mm
SADDLE	SDG BEL AIR Overland 3.0	100 mm (S) 125 mm (M) 150 mm (L) 170 mm (XL)
BOTTOM BRACKET	SHIMANO BB-MT800-PA	200 mm (XXL)
		140 mm Lux-Alloy Rail YT Custom Design
		BB Press Fit 92 24 mm

COLOR: MIZU SILVER, BLACK MAGIC

SIZES: S,M,L,XL,XXL



IZZO 29 CORE 3 CF

	Flipchip position	High					Low				
	Frame size	S	M	L	XL	XXL	S	M	L	XL	XXL
A	Toptube in mm	567	592	617	642	667	568	593	618	643	668
B	Reach in mm	427	449	471	490	512	424	445	467	487	508
C	Stack in mm	604	613	622	636	645	607	616	625	639	648
D	Seattube in mm	400	425	450	475	500	400	425	450	475	500
E	Chainstay in mm	431	431	431	436	436	432	432	432	437	437
F	Headtube angle	66.1 °	66.1 °	66.1 °	66.1 °	66.1 °	65.7 °	65.7 °	65.7 °	65.8 °	65.8 °
G	Seattube angle (eff)	77.0 °	76.9 °	76.8 °	76.6 °	76.5 °	76.6 °	76.5 °	76.4 °	76.2 °	76.1 °
H	BB drop	31	31	32	32	32	36	36	36	36	36
I	Wheelbase in mm	1169	1195	1220	1251	1276	1170	1195	1221	1251	1277
J	Headtube in mm	95	105	115	130	140	95	105	115	130	140
K	BB height in mm	343	343	342	342	342	338	338	338	338	338
L	Standover height in mm	742	734	729	724	742	737	729	724	719	737